DVG6565KR



Freestanding wall decorative cooker hood



P.A.S. System

Timer and refresh

Wall mounted cooker hood Venting with air extraction or recirculation Energy class: D Material of housing/chimney: stainless steel and glass / stainless steel Colour of housing/chimney: White / stainless steel Lightning efficiency class: A Grease filtering efficiency class: E Fluid dynamic efficiency class: E Maximum extraction rate by extraction operation: 463 m3/h Venting tube diameter: 15 cm Air flow by extraction version, step 1: 211 m3/h Air flow by extraction version, step 2: 333 m3/h Air flow by extraction version, step 3: 463 m3/h Electronic control Control setting: Touch control Timer function Number of speed positions: 3 Constant ventilation ReFresh Lamp type: LED On/off light switch Number of lights: 4 Power of lights: 4 W Airflow boost position (PowerBoost 1) - extraction: 623 m3/h Perimetric suction Filter material: Aluminium Grease filter indicator Coal filter code (optional as separate purchase): 322147 Number of filters: 1 Recirculation set number: 330276 Washable grease filter Number of motors: 1 Number of PowerBoost functions: 1 No return airflow flap: 150 mm Max. noise level: 54 dB(A)re 1 pW Height: 523 mm Min. height of the chimney: 465 mm Max. height of the chimney: 916 mm Annual energy consumption: 81.2 kWh Dimensions (W×H×D): 60 × 52.3 × 44.2 cm Dimensions of packed product (W×H×D): 72 × 55 × 63 cm Net weight: 17.2 kg Gross weight: 21.3 kg Consumption in standby mode: 0.6 W Connected load: 204 W Nominal current of fuse: 10 amp Product code: 312583 EAN code: 3838942895838

